

Date : 07/29/2025
Project No : 2024C213
Client Company : WDG
Arrival Time : 07/29/2025 07:00
Onsite Hours : 02:00

ASEC Report ID : 83874
Name of the Project : Covington Town Center PH II
Project Location : Covington, GA
Weather : Partly cloudy
Departure Time : 07/29/2025 09:00
ASEC Technician Name : Austin Coleman

As requested, the site was visited by our AS Engineering and Consulting (ASEC) representative for the purpose of providing quality control inspection and testing services. Visual observation techniques were employed to verify compliance with project drawing/specifications, applicable codes, and materials submittals. The following observations were observed on site this day.

Our ASEC representative arrived on site to observe the placement of 19mmSP asphalt mix for the roadway. Back-scatter density testing was performed on newly placed asphalt following compaction with a smooth-drummed roller. A total of fifteen (15) density tests were taken. The results are stated below:

Test Section #1: 139.1 pcf (left), 137.9 pcf (center), 136.5 pcf (right) [location northwest]

Test Section #2: 139.7 pcf (left), 134.8 pcf (center), 145.0 pcf (right) [location southwest]

Test Section #3: 140.7 pcf (left), 135.9 pcf (center), 134.3 pcf (right) [location southeast]

Test Section #4: 138.5 pcf (left), 133.9 pcf (center), 130.3 pcf (right) [location east]

Test Section #5: 142.3 pcf (left), 140.2 pcf (center), 141.9 pcf (right) [location north]

Note: left, center, right = side of lane tested as oriented to direction of placement.

We appreciate the opportunity to be of service to you on this project. If you have any questions regarding this report, please feel free to contact us. We will be more than happy to discuss it with you.

Date : 07/29/2025
 Project No : 2024C213
 Client Company : WDG
 Arrival Time : 07/29/2025 07:00
 Onsite Hours : 02:00

ASEC Report ID : 83874
 Name of the Project : Covington Town Center PH II
 Project Location : Covington, GA
 Weather : Partly cloudy
 Departure Time : 07/29/2025 09:00
 ASEC Technician Name : Austin Coleman

| Mix Type | 12.5 SP RAP | MIXTURE DATA | Mix Type | 12.5 SP RAP |
|----------|-------------|--------------|----------|-------------|
| 100.0 | | | 100.0 | |
| 99.0 | | | 99.0 | |
| 98.0 | | | 98.0 | |
| 97.0 | | | 97.0 | |
| 96.0 | | | 96.0 | |
| 95.0 | | | 95.0 | |
| 94.0 | | | 94.0 | |
| 93.0 | | | 93.0 | |
| 92.0 | | | 92.0 | |
| 91.0 | | | 91.0 | |
| 90.0 | | | 90.0 | |
| 89.0 | | | 89.0 | |
| 88.0 | | | 88.0 | |
| 87.0 | | | 87.0 | |
| 86.0 | | | 86.0 | |
| 85.0 | | | 85.0 | |
| 84.0 | | | 84.0 | |
| 83.0 | | | 83.0 | |
| 82.0 | | | 82.0 | |
| 81.0 | | | 81.0 | |
| 80.0 | | | 80.0 | |
| 79.0 | | | 79.0 | |
| 78.0 | | | 78.0 | |
| 77.0 | | | 77.0 | |
| 76.0 | | | 76.0 | |
| 75.0 | | | 75.0 | |
| 74.0 | | | 74.0 | |
| 73.0 | | | 73.0 | |
| 72.0 | | | 72.0 | |
| 71.0 | | | 71.0 | |
| 70.0 | | | 70.0 | |
| 69.0 | | | 69.0 | |
| 68.0 | | | 68.0 | |
| 67.0 | | | 67.0 | |
| 66.0 | | | 66.0 | |
| 65.0 | | | 65.0 | |
| 64.0 | | | 64.0 | |
| 63.0 | | | 63.0 | |
| 62.0 | | | 62.0 | |
| 61.0 | | | 61.0 | |
| 60.0 | | | 60.0 | |
| 59.0 | | | 59.0 | |
| 58.0 | | | 58.0 | |
| 57.0 | | | 57.0 | |
| 56.0 | | | 56.0 | |
| 55.0 | | | 55.0 | |
| 54.0 | | | 54.0 | |
| 53.0 | | | 53.0 | |
| 52.0 | | | 52.0 | |
| 51.0 | | | 51.0 | |
| 50.0 | | | 50.0 | |
| 49.0 | | | 49.0 | |
| 48.0 | | | 48.0 | |
| 47.0 | | | 47.0 | |
| 46.0 | | | 46.0 | |
| 45.0 | | | 45.0 | |
| 44.0 | | | 44.0 | |
| 43.0 | | | 43.0 | |
| 42.0 | | | 42.0 | |
| 41.0 | | | 41.0 | |
| 40.0 | | | 40.0 | |
| 39.0 | | | 39.0 | |
| 38.0 | | | 38.0 | |
| 37.0 | | | 37.0 | |
| 36.0 | | | 36.0 | |
| 35.0 | | | 35.0 | |
| 34.0 | | | 34.0 | |
| 33.0 | | | 33.0 | |
| 32.0 | | | 32.0 | |
| 31.0 | | | 31.0 | |
| 30.0 | | | 30.0 | |
| 29.0 | | | 29.0 | |
| 28.0 | | | 28.0 | |
| 27.0 | | | 27.0 | |
| 26.0 | | | 26.0 | |
| 25.0 | | | 25.0 | |
| 24.0 | | | 24.0 | |
| 23.0 | | | 23.0 | |
| 22.0 | | | 22.0 | |
| 21.0 | | | 21.0 | |
| 20.0 | | | 20.0 | |
| 19.0 | | | 19.0 | |
| 18.0 | | | 18.0 | |
| 17.0 | | | 17.0 | |
| 16.0 | | | 16.0 | |
| 15.0 | | | 15.0 | |
| 14.0 | | | 14.0 | |
| 13.0 | | | 13.0 | |
| 12.0 | | | 12.0 | |
| 11.0 | | | 11.0 | |
| 10.0 | | | 10.0 | |
| 9.0 | | | 9.0 | |
| 8.0 | | | 8.0 | |
| 7.0 | | | 7.0 | |
| 6.0 | | | 6.0 | |
| 5.0 | | | 5.0 | |
| 4.0 | | | 4.0 | |
| 3.0 | | | 3.0 | |
| 2.0 | | | 2.0 | |
| 1.0 | | | 1.0 | |
| 0.0 | | | 0.0 | |



WD: 140.4
 PD: 136.5
 MP: 3.9
 %M: 2.4%
 Lx: NWIS
 07/29/2025 DS: 2079 MS: 762
 Covington 19mm SP
 L: 139.1 L: 137.7 L: 140.7
 C: 137.9 C: 134.8 C: 135.9
 R: 136.5 R: 145.0 R: 134.3
 Lx: NW (green) Lx: SW Lx: E
 L: 135.5 L: 142.3
 C: 133.9 C: 140.2
 R: 130.3 R: 141.9
 Lx: E (green) Lx: N (Hisco Mill)

Kenneth Mosman

Kenneth Mosman

The results presented in this report relate only to the items tested. This report shall not be reproduced, except in full, without written approval from AS Engineering and Consulting LLC.